


MASCHI A MACCHINA - MACHINE TAPS

SCANALATURE DIRITTE con IMBOCCO CORRETTO forma "B"
 Filettatura metrica ISO/DIN 13 - UNI 4535 a passo grosso - **6HX**
Universali - per INOX - per materiali ad alta resistenza

STRAIGHT FLUTES SPIRAL POINT (GUN NOSE) - Chamfer form "B"
 ISO Metric Coarse Thread - UNI 4535 - DIN 13 - **6HX**
Universal use - for STAINLESS STEEL - for high resistance materials





<div style="display: flex; flex-direction: column; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #4a4a8a; margin-bottom: 5px;"></div> <div>HSS-Co-PM</div> <div style="width: 15px; height: 15px; background-color: #e67e22; margin-bottom: 5px; margin-top: 10px;"></div> <div>HSSV</div> </div>	Rm 1200 max	Universal		4511.U1 4513.U1
	Rm 1400 max	Hard		4511.X1 4513.X1
	Rm 1000 max	INOX		4511.S1 4513.S1



DIN 371 D ≤ 10mm.

DIN 376 D ≥ 12mm.



DIN 371 / DIN 376							4511.U1	4513.U1	4511.X1	4513.X1	4511.S1	4513.S1
D	p	L ₁	L ₂	d ₂	∠		ASP30 + TX	ASP30 + TX	ASP30 + HPC	ASP30 + HPC	HSSV + HPC	HSSV + HPC
3	0,5	56	10	3,5	2,7	2,50	37,40	-	38,28	-	33,22	-
4	0,7	63	13	4,5	3,4	3,30	37,40	-	38,28	-	33,22	-
5	0,8	70	13	6,0	4,9	4,20	37,40	-	38,28	-	33,22	-
6	1	80	16	6,0	4,9	5,00	37,40	-	38,28	-	33,22	-
8	1,25	90	18	8,0	6,2	6,75	46,53	-	46,75	-	41,25	-
10	1,5	100	20	10,0	8,0	8,50	52,47	-	56,21	-	46,53	-
12	1,75	110	25	9,0	7,0	10,25	-	64,24	-	66,11	-	56,98
14	2	110	28	11,0	9,0	12,00	-	83,27	-	85,91	-	74,36
16	2	110	28	12,0	9,0	14,00	-	102,96	-	96,03	-	79,86
18	2,5	125	33	14,0	11,0	15,50	-	135,30	-	-	-	109,23
20	2,5	140	33	16,0	12,0	17,50	-	164,12	-	-	-	132,22
22	2,5	140	33	18,0	14,5	19,50	-	194,70	-	-	-	-
24	3	160	39	18,0	14,5	21,00	-	225,72	-	-	-	-

NEW

Altre dimensioni su richiesta / Other dimensions on demand

Materiali / Application: 4511.U1 - 4513.U1: P1 - P2 - P3 - P4 - P5 / M1 - M2 - M3 / K3 - K4 / N2 - N3 / N7
 4511.X1 - 4513.X1: P5 - P6 / K3 - K4 / N4 / N8
 4511.S1 - 4513.S1: P3 - P4 - P5 / M1 - M2 - M3 - M4